Network Security: Public Key Infrastructure

Guevara Noubir Northeastern University noubir@ccs.neu.edu Network Security

Slides adapted from Radia Perlman's slides



Key Distribution - Secret Keys


- What if there are millions of users and thousands of servers?
- Could configure n² keys
- Better is to use a Key Distribution Center
 - Everyone has one key
 - The KDC knows them all
 - The KDC assigns a key to any pair who need to talk

Network Security

PKI

2

Key Distribution - Secret Keys Alice KDC Bob A wants to talk to B Randomly choose Kab {"B", Kab}Ka {"A", Kab}Kb {Message}Kab




-

KDC Realms

- KDCs scale up to hundreds of clients, but not millions
- There's no one who everyone in the world is willing to trust with their secrets
- KDCs can be arranged in a hierarchy so that trust is more local

Network Security

PKI





KDC Hierarchies

- In hierarchy, what can each compromised KDC do?
- What would happen if root was compromised?
- If it's not a name-based hierarchy, how do you find a path?

Network Security

DKI

-



Key Distribution - Public Keys

- Certification Authority (CA) signs "Certificates"
- Certificate = a signed message saying "I, the CA, vouch that 489024729 is Radia's public key"
- If everyone has a certificate, a private key, and the CA's public key, they can authenticate

Network Security

PKI

8



KDC vs CA Tradeoffs

- Impact of theft of KDC database vs CA private key
- What needs to be done if CA compromised vs. if KDC compromised?
- What if KDC vs CA down temporarily?
- What's more likely to work behind firewalls?

Network Security

PKI



Strategies for CA Hierarchies

- One universally trusted organization
- Top-Down, starting from a universally trusted organization's well-known key
- No rules (PGP, SDSI, SPKI).
 - Anyone signs anything. End users decide who to trust
- Many independent CA's.
 - Configure which ones to trust

Network Security

10



One CA

- Choose one universally trusted organization
- Embed their public key in everything
- Give them universal monopoly to issue certificates
- Make everyone get certificates from them
- Simple to understand and implement

Network Security

PK

11



One CA: What's wrong with this model?

- Monopoly pricing
- Getting certificate from remote organization will be insecure or expensive (or both)
- That key can never be changed
- Security of the world depends on honesty and competence of the one organization, forever

Network Security

PKI

1
_



One CA Plus RAs

- RA (registration authority), is someone trusted by the CA, but unknown to the rest of the world (verifiers).
- You can request a certificate from the RA
- It asks the CA to issue you a certificate
- The CA will issue a certificate if an RA it trusts requests it
- Advantage: RA can be conveniently located

Network Security

DK

13



What's wrong with one CA plus RAs?

- Still monopoly pricing
- Still can't ever change CA key
- Still world's security depends on that one CA key never being compromised (or dishonest employee at that organization granting bogus certificates)

Network Security

PKI

14




Oligarchy of CAs

- Come configured with 50 or so trusted CA public keys
- Usually, can add or delete from that set
- Eliminates monopoly pricing

Network Security

PKI





What's wrong with oligarchy?

- Less secure!
 - Security depends on ALL configured keys
 - Naïve users can be tricked into using platform with bogus keys, or adding bogus ones (easier to do this than install malicious software)
- Although not monopoly, still favor certain organizations

Network Security Pi

17



CA Chains

- Allow configured CAs to issue certs for other public keys to be trusted CAs
- Similar to CAs plus RAs, but
 - Less efficient than RAs for verifier (multiple certs to verify)
 - Less delay than RA for getting usable cert

Network Security

PKI



Anarchy

- Anyone signs certificate for anyone else
- Like configured+delegated, but users consciously configure starting keys
- Problems
 - Does not scale (too many certs, computationally too difficult to find path)
 - No practical way to tell if a path should be trusted
 - Too much work and too many decisions for user

Network Security

PK

19



Name Constraints

- Trustworthiness of a CA is not binary
 - Complete trust or no trust
- CA should be trusted for certifying a subset of the users
- Example:
 - Northeastern University CCS should (only) be trusted to certify users with name x@y.ccs.neu.edu
- If users have multiple names, each name should be trusted by the "name authority"

Network Security

PKI

20



Top Down with Name Subordination

- Assumes hierarchical names
- Similar to monopoly: everyone configured with root key
- Each CA only trusted for the part of the namespace rooted at its name
- Can apply to delegated CAs or RAs
- Easier to find appropriate chain
- More secure in practice
 - This is a sensible policy that users don't have to think about)

Network Security

PKI





Bottom-Up Model


- Each arc in name tree has parent certificate (up) and child certificate (down)
- Name space has CA for each node in the tree
 E.g., a certificate for .edu, neu.edu, and ccs.neu.edu
- "Name Subordination" means CA trusted only for a portion of the namespace
- Cross Links to connect Intranets, or to increase security
- Start with your public key, navigate up, cross, and down

Network Security

PK









Advantages of Bottom-Up

- For intranet, no need for outside organization
- Security within your organization is controlled by your organization
- No single compromised key requires massive reconfiguration
- Easy configuration:
 - you start with is your own public key

Network Security

PKI

26



Bridge CA Model

- Similar to bottom-up, in that each organization controls its destiny, but top-down within organization
- Trust anchor is the root CA for your org
- Your org's root points to the bridge CA, which points to other orgs' roots

Network Security

PKI

u
_



Chain Building

- Call building from target "forward", and from trust anchor "reverse"
 - With the reverse approach it can be easier to find a path from the anchor to A by looking at the path
 - With the forward approach "going up" we don't know if a link/path starting at A leads to a trust anchor known by B
- Where should cert be stored?
 - With subject: harder to build chains from trust anchors
 - With issuer: it may become impractical if large fanout at root

Network Security

PKI

28



X.509

- An authentication framework defined by ITU
- A clumsy syntax for certificates
 - No rules specified for hierarchies
 - X.509 v1 and v2 allowed only X.500 names and public keys in a certificate
 - X.509 v3 allows arbitrary extensions
- A dominant standard
 - Because it is flexible, everyone willing to use it
 - Because it is flexible, all hard questions remain
- C: country, CN: common name, O: organization, etc.

Network Security

PKI

29



X.509 Certificate Contents

- version # (1, 2, or 3)
- Serial Number
- Effective Date
- Expiration Date
- Issuer Name
- Issuer UID (not in V1)
 - Unique ID
- Subject Name
- Subject UID (not in V1)
- Subject Public Key Algorithm
- Subject Public Key
- Signature Algorithm
- Signature
- Extensions (V3 only)

Natwork Security

DIT

1	$^{\circ}$	
1	v	



Some X.509 V3 Extensions

- Public Key Usage
 - Encryption
 - Signing
- Key Exchange
- Non-repudiation
- Subject Alternate Names
- Issuer Alternate Names
- Key Identifiers
- Where to find CRL information
- Certificate Policies
- "Is a CA" flag
 - path length constraints
 - name constraints
- Extended key usage
- specific applications

Network Security

PKI

31



Policies

- A policy is an OID:
 - Code Signing (1.3.6.1.5.5.7.3.3),
 - Windows Hardware Driver Verification (1.3.6.1.4.1.311.10.3.5)
- Verifier specifies required OIDs

Network Security

PKI

32



Policies (as envisioned by X. 509/PKIX)

- Policy is an OID (Object Identifier) e.g., top-secret, or secret
- Verifier says what policy OID(s) it wants
- Every link must have same policy in chain, so if verifier wants A or B or C, and chain has A, AC, ABC, B: not OK
- Policy mapping: A=X; "want A" AB, A, A=X, X, X...
- "Policy constraints" things like:
 - policies must appear, but it doesn't matter what they are
 - "any policy" policy not allowed
 - any of these, but specified as taking effect n hops down chain

Network Security

PK



Other Certificate Standards

- PKIX: http://www.ietf.org/html.charters/pkix-charter.html
 - An IETF effort to standardize extensions to X.509 certificates
 - PKIX is a profile of X.509
 - Still avoids hard decisions, anything possible with PKIX
- SPKI: http://www.ietf.org/html.charters/spki-charter.html
 - Simple Public Key Infrastructure
 - A competing IETF effort rejecting X.509 syntax
- SDSI: http://theory.lcs.mit.edu/~cis/sdsi.html
 - Simple Distributed Security Infrastructure
 - · A proposal within SPKI for certificates with relative names only

Network Security

DKI



Revocation Problem

- Suppose a bad guy learns your password or steals your smart card...
- Notify your KDC and it will stop issuing "tickets"
- Notify your CA and it will give you a new certificate
- How do you revoke your old certificate?

Network Security

PKI

35



Revocation Problem

- Tickets can have short lifetimes; they can even be "one-use" with nonces
- Certificates have expiration dates, but it is inconvenient to renew them frequently
 - If sufficiently frequent and automated, CA can no longer be off-line
- Supplement certificate expirations with Certificate Revocation Lists (CRLs) or a blacklist server (On-Line Revocation Server: OLRS)

Network Security

PKI

- 1	_
- 1	



Why not put CA on-line?

- On-line revocation server is less security sensitive than an on-line CA
- The worst it can do is fail to report a revoked certificate
- Damage is more contained
- Requires a double failure
- With CRLs, limits OLRS damage

Network Security



Revocation Ideas

- Incremental (delta) CRLs
- Micali's hashing scheme
- Kaufman-Perlman "first valid cert"
- Good lists vs bad lists

Network Security



Micali's Hashing

- Components:
 - CA: generates/revokes certificates
 - Directory:
 - Gets daily updates from the CA and gets requests from users
 It is not trusted
- Technique for efficient revocation:

 - CA generates:
 Computes: Y_n = Hashⁿ(Y₀) and N_n = Hashⁿ(N₀), where Y₀, and N₀ are secret values
 Certificate = signature of traditional info (e.g., public key, issue date, etc.) and Y_n and N_i; 100 bits messages unique to the certificate. n is the certificate lifetime
 Every day i the CA sends the directory:
 Y_n, or N_n, depending on if the certificate is revoked or not



Authorization

- Access Control Lists (ACL) capabilities:
 - Makes a difference whether you can answer "who has access to that" or "what can he do"
- Groups, nesting, roles
- On-line group servers
- Anonymous groups

Network Security

DKI

40



Suppose want to move subtrees?

- How would you design certificates if you want to be able to move an entire subtree, for example, com.sun.east.labs.radia becomes com.sun.labs.radia.
- What would up, down, and cross certs look like? How design cross link if want things not to change if both points move together?

Network Security

PKI